ST

DEFENDER, penetrating sealer for stones.

Low Vapour Pressure VOC compliant solvent based stain blocking penetrating sealer. That protects and preserves the appearance of porous natural stones, such as slate, marble, limestone, terrazzo, and granite, without adding gloss, while acting as protective, dirt-resistant penetrating sealer, without making the surface slippery. Allows the surface to breath naturally. No significant colour change and does not change gloss level.

LONGLASTING result.

Suitable for interior and exterior applications.

APPLICATION

porous natural stones, such as slate, marble, limestone, tumbled marble, travertine, granite, terrazzo, etc..

DIRECTIONS FOR USE

The surface to be treated should be dry, clean and free from dust. Before applying the product, ensure all of the above. Apply the product in a thin layer by using a paintbrush or roller. Allow to dry fro 8 to 15 minutes before removing residue. If . necessary apply a second coat. To achieve a slight gloss, buff with synthetic white pad. Do NOT use on sealed, glazed, polished or non-absorbtive surfaces. Allow good ventilation.

Do NOT over-apply. In case of over-application use solvent, mineral spirits, turpentine or HG SpotStain Remover.

PRODUCT INFORMATION.

Colourless, trans	sparant liquid. Combustible liquid.	
s.g.	n/a	
pH	n/a	Manufactured by:
compositions	petroleum distillate plus proprietary oil.	Solstrand Trading
Usage	from 200-400 sq/ft per liter, depending	60 Lockhart Road,
SIZES AVAILABLE	absorption.	Barrie, Ontario, Canada
12 x 1.0 liter	art: 271101164	L4N 9G8
4 x 4.0 liter	art: 271401164	Tel: 1-705-726-5445
1 x 10 liter	art: 271911164	Fax: 1-705-734-0857
CAUTION		www.hgmaintenance.com
Flammable.		guality@hgmaintenance.com

Flammable. Keep out of reach for children. MSDS per request.

PROFESSIONAL MAINTENANCE AND STONE RESTORATION SYSTEMS

