Material Safety Data Sheet

HG hygienic fridge cleaner



1. Product and company identification

Product name : HG hygienic fridge cleaner

Supplier : Solstrand Trading

60 Lockhart Road

Barrie, ON.

Tel: (705)726-5445 www.hgmaintenance.com

Trade name : HG hygienic fridge cleaner

Material uses : Not available.

Manufacturer : HG International BV

Damsluisweg 70 - NL-1332 EJ - Almere - The Netherlands

+31 36 54 94 700

Code : 335 **MSDS #** : 1

 Validation date
 : 25-4-2013.

 Print date
 : 25-4-2013.

In case of emergency : +31 (0)36 54 94 777

Product type : Liquid.

2. Hazards identification

Emergency overview

Physical state : Liquid.

Color : Colorless to light yellow.

Odor : Fragrance-like.
Signal word : WARNING!

Hazard statements : FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Precautionary measures : Do not handle until all safety precautions have been read and understood. Obtain

special instructions before use. Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly

closed. Use personal protective equipment as required. Wash thoroughly after

handling.

Routes of entry : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin : Moderately irritating to the skin.

Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects : Contains material that can cause target organ damage.

Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity : No known significant effects or critical hazards.Teratogenicity : No known significant effects or critical hazards.

2. Hazards identification

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: No known significant effects or critical hazards.

Target organs

Contains material which causes damage to the following organs: eye, lens or cornea. Contains material which may cause damage to the following organs: blood, kidneys, the nervous system, the reproductive system, liver, spleen, upper respiratory tract, skin, central nervous system (CNS).

Over-exposure signs/symptoms

Inhalation : No specific data. Ingestion : No specific data.

Skin : Adverse symptoms may include the following:

> irritation redness

Eyes : Adverse symptoms may include the following:

> pain or irritation watering redness

Medical conditions aggravated by overexposure

Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
Ethanol	64-17-5	25 - 50
2-Propanol	67-63-0	1 - 2.5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Inhalation

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water **Eye contact** for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is

> suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

No specific treatment. Treat symptomatically. Contact poison treatment specialist Notes to physician immediately if large quantities have been ingested or inhaled.

25-4-2013. 2/1

5. Fire-fighting measures

Flammability of the product

: Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable

: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable

: Do not use water jet.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire

Not available.

hazards

: Not available.

Special remarks on explosion hazards

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original

25-4-2013. **3/1**0

7. Handling and storage

container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours) STEL (15 mins)		Ceiling							
Ingredient List name		ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Ethanol	US ACGIH 3/2012	-	-	-	1000	-	-	-	-	_	
	AB 4/2009 BC 4/2012	1000	1880	-	1000	-	-	-	-	-	
	ON 7/2010 QC 9/2011	- 1000	- 1880	_	1000	-	-	-	-		
2-Propanol	US ACGIH 3/2012	200	-	_	400	-	-	-	-	_	
	AB 4/2009 BC 4/2012	200	492	_	400 400	984	- -	-	-	_	
	ON 7/2010	200	-	-	400	-	-	-	-	-	
	QC 9/2011	400	983	-	500	1230	-	-	-	 	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

25-4-2013. **4/1**0

8. Exposure controls/personal protection

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other protection

Personal protective
equipment (Pictograms)

Not available.



9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: 28°C (82,4°F)

Burning time : Not applicable.

Burning rate : Not applicable.

Auto-ignition temperature : 370°C (698°F)

Flammable limits : Not available.

Color : Colorless to light yellow.

Odor : Fragrance-like.

Taste : Not available.

Molecular weight : Not applicable.

Molecular formula : Not applicable.

pH : 9

Boiling/condensation point: Not available.Melting/freezing point: Not available.Critical temperature: Not available.

Relative density : 0,942

Vapor pressure : Not available.
Vapor density : Not available.

Volatility : 49.61% (v/v), 36.92% (w/w)

Odor threshold : Not available.

Evaporation rate : Not available.

25-4-2013. *5/1*0

9. Physical and chemical properties

SADT : Not available.

Viscosity : Not available.

Ionicity (in water) : Not available.

Dispersibility properties : Not available.

Solubility : Easily soluble in the following materials: cold water and hot water.

Physical/chemical properties comments

: Not available.

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
2-Propanol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Conclusion/Summary

: Not available.

Chronic toxicity

Not available.

Conclusion/Summary

: Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0,066666667 minutes 100	-
	Eyes - Moderate irritant	Rabbit	-	milligrams 100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
2-Propanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant Eyes - Severe irritant	Rabbit Rabbit	-	10 milligrams 100 milligrams	-

25-4-2013. 6/10

11. Toxicological information

	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	

Conclusion/Summary

: Not available.

Sensitizer

Not available.

Conclusion/Summary

: Not available.

Carcinogenicity

Not available.

Conclusion/Summary: Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Ethanol	A3	1	-	-	-	-
2-Propanol	A4	3	-	-	-	-

Mutagenicity

Not available.

Conclusion/Summary: Not available.

Teratogenicity

Not available.

Conclusion/Summary: Not available.

Reproductive toxicity

Not available.

Conclusion/Summary : Not available.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity : Readily biodegradable

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Ethanol	Acute EC50 17,921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
		franciscana - Larvae	
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4,995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0,375 ul/L Fresh water	Fish - Gambusia holbrooki -	12 weeks
	·	Larvae	
2-Propanol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
-	Acute LC50 1400000 μg/l	Fish - Gambusia affinis	96 hours

Conclusion/Summary

: Readily biodegradable

Persistence/degradability

Not available.

Conclusion/Summary : Readily biodegradable

Partition coefficient: n-

octanol/water

: Not available.

Bioconcentration factor

: Not available.

25-4-2013. 7/10

12. Ecological information

Mobility : Not available. Toxicity of the products of

biodegradation

Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream Not available. **RCRA** classification : Not available.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	PLANIMATE HOUT	-
TDG Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	***	-
Mexico Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	***	-
ADR/RID Class	UN1993	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	3	Hazard identification number 30 Limited quantity 5 L Special provisions 640 (E) Tunnel code (D/E)

25-4-2013. 8/11

14. Transport information

IMDG Class	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	8	Emergency schedules (EmS) F-E, S-E
IATA-DGR Class	FLAMMABLE LIQUID, N.O.S. (2-Propanol, Ethanol, mixture)	3	III	1	-

PG*: Packing group

15. Regulatory information

United States inventory

(TSCA 8b)

All components are listed or exempted.

WHMIS (Canada)

: Class B-2: Flammable liquid

Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Ethanol; Isopropyl alcohol

CEPA Toxic substances : None of the components are listed. **Canada inventory** : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

: Australia inventory (AICS): All components are listed or exempted. China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted. Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

Chemical Weapons Convention List Schedule

I Chemicals

: Not listed

Chemical Weapons Convention List Schedule

II Chemicals

: Not listed

Chemical Weapons

Convention List Schedule

: Not listed


III Chemicals

16. Other information

Label requirements

FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Hazardous Material Information System (U.S.A.)



25-4-2013. 9/11

16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



References : Not available.

Other special : Not available.

considerations

Date of printing : **25-4-2013**. **Qate of issue** : 25-4-2013.

Date of previous issue : No previous validation.

Version : 1

Prepared by : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.