

STONE & MARBLE/GRANITE PROTECTOR.

Waterbased and complete VOC-FREE sealer, that provides completely colorless, invisible protection on low absorptive surfaces, like polished marble polished granites, even fullbody porcelain tile.

Repells water, oil/grease, limescale and reduces the risks of discoloration, efflorescence, frost damage, mould and algae growth and erosion.

May be used overtop HG Stone & Marble Penetrating Sealer

APPLICATION

The surface must be completely clean and dry
Apply Stone & Marble Protector undiluted with a paint roller or
lint-free cloth. On verticle surfaces, start from the bottom up.
Low pressure spraying allowed. Keep away from flames.
Apply in one direction. Do not treat more then 6-8 m2 /60-80 sq/ft
at a time, or more if working with larger crew.
After approx. 10 minutes, and before it has time to dry up
on top the surface, remove any surplus from the surface.
If all sealer soaked in, apply a second coat 1 hour after first coat,
again removing any possible surplus within 10 minutes.
Allow final coat to dry for min. 3 hr. for any light foot traffic, or
24 hours before allowing any liquid spills or cleaning.

for further protection over higher absorptive surfaces.

ATTENTION

This waterbased product may NOT be mixed with other and/or solventbased penetrating sealers. To avoid possible colour differences, do NOT use this product adjacent other penetrating sealers. This product may be used overtop fully dried solventbased penetrating sealers, to further protect from dirt.

COVERAGE

5-10 m2 / 50-100 sq/ft per 0.25 liter. 100-200 m2 / 1000 - 2000 sq/ft per 5.0 litre Coverage depends strongly on porousity of stone.

PRODUCT INFORMATION.

flashpoint n/a relative density 1.006 g/ml

Usage approx.50-100 sq/ft per 0.25 litre

compositions waterbased

pH 4.2

SIZES AVAILABLE

6 x 0.25 Ltr # 580-025 4 x 5.0 Ltr # 580-500

CAUTION

Keep out of reach for children. Avoid contact with eyes.

Rinse splashes in the eyes with plenty of water. Upon swallowing, drink plenty of water and seek medical advice. Do NOT allow liquid to dry on the surface, but always remove beforehand (within about 10 minutes)

WARRANTY

Warranty Disclaimer: HG International b.v. and Solstrand Trading Inc.warrants that its products will be merchantable at the time of shipment. This warranty is made in place of any other warranty. HG International b.v. and Solstrand Trading Inc. expressly disclaims any warranty of fitness for a particular purpose.

Limitations of Remedies: If properly notified (as required by HG International b.v. return good policy), HG International b.v. and Solstrand Trading Inc. will replace any product which HG International b.v. and Solstrand Trading Inc. determines was defective at the time of shipment to the customer. This replacement remedy is the customer's exclusive remedy against HG International b.v. and Solstrand Trading Inc. for any property damage caused by any defect or other failure in the products. Under no circumstances is HG International b.v. and Solstrand Trading Inc. liable for any direct, incidental, special or consequential damages (including lost profit) in any way relating to the product or this agreement.





Solstrand Trading Inc. 2871 Brighton Road Oakville, Ontario L6H 6C9

Tel: (905) 257-7110 Fax: (905) 829-9914 www.hgcanada.com

Manufactured by: HG International, b.v. Almere, Netherlands