

HG

TOP PROTECTOR, waterbased sealer for granite and other stone countertops

Odourless, invisible protection and dirt delaying action particularly against (edible) oils, vegetable and animal fats, and other kinds of dirt. The best protection can be achieved by applying HG Top Protector otop of HG Marble & Stone Protector or other solventbased penetrating sealers. Great for countertops and vanities.

APPLICATION Re-apply from time to time.

Ideal on most absorptive surfaces, like marble, travertine, slate, limestone, sandstone, but also granite.

Best result when used otop solventbased sealers.

DIRECTIONS for use:

The surface must be completely clean and dry. Apply HG Top Protector neat and undiluted with enclosed cloth or brush. On verticle surfaces, start from the bottom up. Apply in one direction.

After approx. 5 minutes, and before it has time to adhere to the surface, remove any surplus from the surface.

Allow to dry for approx. 2 hours before applying a second coat
If Necessary. Do not allow liquid spills for at least 12 hours.

COVERAGE

up to. 10 m2 / 100 sq/ft per 100 ml., depending absorption.

SIZES AVAILABLE

6 x 100 ml.

272-010



PRODUCT INFORMATION

relative density	1.013 gr/ml
flashpoint	approx. 34C.
Components	fluorocarbons and solvents

CAUTION

Keep out of reach for children. Avoid contact with eyes.
Rinse splashes in the eyes with plenty of water. Upon swallowing, drink plenty of water and seek medical advice.
Do NOT induce vomiting.

Solstrand Trading
60 Lockhart Road,
Barrie, Ontario, Canada
L4N 9G8

www.hgmaintenance.com

Tel: 1-705-726-5445

Fax: 1-705-734-0857

Manufactured by:
HG International, b.v.
Almere, Netherlands

HG PROFESSIONAL STONE MAINTENANCE AND RESTORATION SYSTEMS